



KRAFT TAPE



Item	Physical performance	Standard	Application
Thickness(μ)	130±10	GB/T7125-2014	It's applicable to the carton packaging and the connections of paper processing.
Initial tack (mm)14#	Summer: ≥50 Winter: ≤200	GB/T4852-2002	
Peel strength (S/S) (N/25mm)	—	GB/T2792-1998	
Peel strength (S/S) (N/24mm)	Summer: ≥16/It's damaged on the steel plate Winter: ≥15/It's damaged on the steel plate	GB/T2792-2014 (dwell 20min)	
Holding power (min/24×24mm)	Summer: ≥120 Winter: ≥60	GB/T4851-2014	
Tape color	Khaki	—	
Temp. resistance	Normal use	—	
Carrier	—	—	
Release liner	Kraft paper	—	
Release force	Good	—	

(1) Please ensure the tape is suitable for the particular application before using it. This hot melt pressure-sensitive adhesive tape is not suitable for bonding PVC signs or leather. On the other hand, please confirm the scope after use. The adhesive tape must isolate nonstick material to prevent adhesion after packing or cutting. Shrink films for packaging are NOT allowed.

(2) Confirm the application range of the adhesive tape before using it. 13°C to 33°C will be the ideal temperature for application. We do not suggest using tapes below 10 Celsius because they will become too firm to adhere easily. ☹

On1Shelf® is Trademark of Digital Isle Limited
Unit 15, Cowan's Yard
39 Newtown Road, Camlough, BT35 7JJ
Tel: 02830278150 Fax: 02830278150
E-mail: sales@on1shelf.com